



Hi-Cera Pump[®] V

**Precision valveless
plunger pump**



The Heart of Industry

Ultra-high precision valveless plunger pump

The Iwaki Hicera pump is a compact metering pump that employs a fine ceramic plunger. The unique valveless construction eliminates problems caused by clogging and jamming that commonly occur in conventional metering pumps. The precision micron-machining on the main ceramic parts ensures a high degree of discharge accuracy. The versatility of the Iwaki Hicera pump makes it ideal for micro-chemical feeding as well as high-viscosity liquid feeding.

Ultra-high precision dosing of ±0.5%

Capable of ultra-high precision dosing at a micro discharge capacity. Simple adjustment of the discharge capacity by changing the angle of the pump head.

Higher corrosion resistance—Perfect for handling a variety of liquids

Ceramics and PTFE resins are used on the wetted surface, lending greater resistance when pumping acid, alkaline, organic solvents, and other liquids.

Max. 20,000 mPa-s high viscous liquid transfer

The unique valveless structure enables the smooth metering transfer of high viscous liquid at a maximum of 20,000 mPa-s.

• Discharge accuracy may deteriorate when handling 500 mPa-s or more. If the liquid to be handled contains slurry, make sure to check the properties of the liquid. Contact us for details.
• Contact us for details about pumping highly viscous liquids (20,000 mPa-s or more).

Compact design—Ideal for built-in applications

The compact and light Hicera pumps can be installed in both vertical and horizontal orientations, making them ideal for built-in applications. The reversible motor direction allows you to reverse the flow without needing to change the piping.

Discharge into a vacuum and suction from high pressure sources


Because there are no suction / discharge valves, the pump is able to discharge directly into a vacuum (negative pressure) without the need for electromagnetic valves. Maintains a constant flow even if the suction / discharge pressure fluctuates.

Original structure—Gas lock free

This pump enables air to be automatically discharged from the outlet, thereby preventing problems caused by gas lock.


• Depending on the installation conditions or the liquid being handled, there are times gas cannot be discharged smoothly. Contact us for more details.

Ultra-high precision mechanism



The plunger is connected to the drive joint via a special bearing and pin. When the drive joint rotates, the plunger rotates and moves up and down inside the cylinder. The plunger angle determines how far down the cylinder the plunger moves while the driving joint rotates. This unique structure eliminates the need for the valve system normally employed in other pumps.

Performance graph



Applications

Secondary cell

Filling and pumping the electrolyte solutions of a lithium cell
Injection of gel-like liquid at a constant rate

Paper manufacturing

Injection of paper strength additives at a constant rate
Injection of dye at a constant rate
Injection of slime control agent

Capacitor


Injection of phosphoric acid liquid

Liquid waste treatment facility

Injection of polymer flocculants / slaked limes

Cleaning equipment

Injection of detergent / rinsing chemical




Max. discharge capacity : 2.8/3.4 mL/min
Max. discharge pressure : 0.7 MPa
(50/60Hz)

Max. discharge capacity : 338/406 mL/min
Max. discharge pressure : 0.7 MPa
(50/60Hz)

Max. discharge capacity : 1,400/1,682 mL/min
Max. discharge pressure : 0.5 MPa
(50/60Hz)

Materials

Model	V-05	V-10	V-15
Pump head	SCS14		SUS304
Plunger	SiC	SiC Al ₂ O ₃	SiC Al ₂ O ₃
Cylinder	SiC	SiC Al ₂ O ₃	SiC Al ₂ O ₃
Head seal	PTFE		
Back sheet	PTFE		
Tube joint	SUS316		
Joint seal	PTFE		
Lip seal	PTFE		




Plunger
The plunger is processed using micron order high-precision technology, leading to a higher degree of discharge precision. It is made of SiC or alumina ceramic (Al₂O₃).





Cylinder
Like the plunger, the cylinder is also processed using high-precision technology.



Joint seal
Tube joint
We offer a standard stainless steel hose joint (SUS316) and a stainless steel female adapter (SUS) that can be connected to commercial tube fitting.



Pump head
Head seal



Identification

V	-	05	S	L	P	1	A	1	-	X
1		2	3	4	5	6	7			8

Standard combination	1 Plunger diameter	2 Material (Plunger/Cylinder material)	3 Pump head material	4 Flushing port
05SL	05: Ø5mm	S: SiC/SiC	L: SCS14 Stainless steel casing	_ : Unavailable P : Available
05SLP				
10AL	10: Ø10mm	A: Al ₂ O ₃ /Al ₂ O ₃	L: SCS14 Stainless steel casing	_ : Unavailable P : Available
10ALP				
10SL		S: SiC/SiC		
10SLP				
15AS	15: Ø15mm	A: Al ₂ O ₃ /Al ₂ O ₃	S: SUS304 Machined	_ : Unavailable P : Available
15ASP				
15SS		S: SiC/SiC		
15SSP				

The table above lists the plunger diameter, plunger / cylinder materials, and pump head materials. It also indicates whether a flushing port is equipped.

- 5 Joint**.....Adaptation pump
 - 1: Ø6 SUS hoseV-05, V-10 Gear ratio 1/150 - 1/30
 - 2: Ø10 SUS hose.....V-10 Gear ratio 1/7.5 - 1/3
 - 3: Ø13 SUS hose.....V-15
 - 4: Rc1/4 SUS female adapter.....V-05, V-10
 - 5: Rc3/8 SUS female adapter.....V-15
- 6 Gear ratio**.....Adaptation pump
 - A: 1/150.....V-05, V-10
 - B: 1/75V-05
 - C: 1/30V-10
 - E: 1/7.5.....V-10, V-15
 - G: 1/3V-10, V-15
- 7 Power voltage**
 - 1: AC100V single phase
 - 3: AC200V three phase
- 8 Special specifications**
 - X: Special specifications Contact us for details.

Specifications (50/60Hz)

Model	Gear ratio ^{Note3}	Rotation speed rpm	Max. discharge capacity mL/min	Max. discharge pressure MPa	Tube joint ^{Note4} mm	Standard motor ^{Note5}	Mass kg
V-05SL1A1 ^{Note1}	1/150	9/11	1.3/1.6	0.7	Ø6 SUS316 made hose joint type	Induction motor AC100V 15W AC200V three phase	2.7
V-05SL1B1 ^{Note1}	1/75	19/23	2.8/3.4				
V-10 □ L1A1 ^{Note2}	1/150	9/11	6.0/7.0	0.7	Ø6 SUS316 made hose joint type	Induction motor AC100V 25W AC200V three phase	2.7
V-10 □ L1C1 ^{Note2}	1/30	48/58	33/40				
V-10 □ L2E1 ^{Note2}	1/7.5	193/232	135/162	0.6	Ø10 SUS316 made hose joint type	Induction motor AC100V 40W AC200V three phase	3.1
V-10 □ L2G1 ^{Note2}	1/3	483/580	338/406				
V-15 □ S3E1 ^{Note2}	1/7.5	193/232	559/672	0.5	Ø13 SUS316 made hose joint type	Induction motor AC100V 40W AC200V three phase	8.8
V-15 □ S3G1 ^{Note2}	1/3	483/580	1,400/1,682				

Note1 : The fitting type and motor power supply can be selected. Please refer to the identification for details.
 Note2 : The model code is entered in the □ box (A: Al₂O₃, S: SiC).
 Note3 : The number of revolutions in the table is when the pump load is small, and may decrease as the load increases.
 Note4 : Stainless steel (SUS) female adapters as well as a standard tube joint can be used. (V-05, V-10 : Rc1/4, V-15 : Rc3/8)
 Note5 : Other motors can be used to accommodate non-standard orders. Contact us for details.

- The performance values in the table represent the values for when clear water is pumped at an ambient temperature.
- Discharge capacity per revolution: approx. 0.15 mL/rev for V-05 (swing angle of 18 degrees), approx. 0.70 mL/rev for V-10, approx. 2.90 mL/rev for V-15 (swing angle of 20 degrees)
- The suction ability of the pump is more than 4 meters. Note that suction ability varies depending on the liquid that is used.
- Be sure to clean the inside of the pump when transferring crystalline liquid or liquid that easily sticks. We also recommend using a flushing port.

Special specification examples

Specifications for special motors

Special specifications are required for non-standard motors. Contact us for details about these specifications.

Stepping motor type

Allows for high precision injection at the ultra-precision level. (Repeatability ± 0.5%)



Speed control motor type

(Equipped with a controller)
The variable volume controller located at the top of the motor makes it easy to control the number of the revolutions.



Secondary / lithium cell

Pump equipped with a pump head adjustment mechanism

This type has an adjustable knob used to change the swing angle of the pump head, allowing for the accurate adjustment of the stroke length.



Dialyzer

Pump for artificial dialysis



V-15 for drug solution / dialysate



V-10 for drainage / dialysate



V-10 for drainage / dialysate

This type consists of a PVDF pump head and 24 VDC stepping motor. It is mounted on an artificial dialyzer for use as a ultrafiltration pump or dialysate pump.

Compact and ideal for device installation

V-05 / 07 series

The compact and lightweight V-05 / 07 series is a compact plunger pump that is ideal for incorporating into equipment. Since it is driven by a DC motor, highly accurate discharge rate control is possible. It has a variable discharge rate function and a flushing port can be selected, so it is possible to inject chemicals cleanly. Since there are a wide variety of fittings, it can be incorporated into various devices.

Variable discharge volume

The discharge amount per rotation can be selected by adjusting the swing angle of the pump head. (Select when ordering) See the specifications on page 6 for details.

Note : V-07AF4 is not included.

Flushing port

The cleaning/flush port prevents seizing of the plunger. The plunger surface is kept clean at all times, allowing it to operate freely whenever needed.


Note : V-07AF4 is not included.


High torque motor

Employing bipolar stepping motor, generating approximately twice the torque at the same current value as compared to the conventional unipolar. Trouble such as plunger lock is solved. (V-07 only)

Rotation sensor

With an integrated standard rotation sensor, the pump quickly detects errors and easily monitors discharge rates. (V-07 only)





V-07AF4

Fuel Cell-Only Pump

Application : Fixed-quantity injection of fuel-cell reformed water

Long life design, Low power consumption, lightweight

V-07AF4 is a long-life design with a design life of 95,000 hours. (Conventional type "V-07AF3": 90,000 hours)
Features a lightweight design utilizing an aluminum die cast frame, and includes a lock-type connector on the motor and sensor.



V-05ZF(P)66-P

V-07AEP06-P

V-07AF(P)66-P

V-07AF66-P01

High precision metering pump optimized for immunoassay analyzers

Application : Injection of reagent, cleaning solution, buffer solution, saline solution, etc.

High corrosion resistance

PVDF or ECTFE is used for the pump head material. Supports the transfer of strong alkaline.



V-07AFP06-P

High precision metering pump optimized for dialysis machines

Application : Delivery of A and B dialysates and ultrafiltration

High-temperature capability



Can be cleaned with water as hot as 95°C.

Materials

	V-05ZF	V-07AE	V-07AF
Pump head	PVDF	ECTFE	PVDF
Plunger	ZrO ₂	Al ₂ O ₃	Al ₂ O ₃
Cylinder	Al ₂ O ₃	Al ₂ O ₃	Al ₂ O ₃

Optional accessory

Conversion joints for V-07AEP06-P

Connect with commercially available fittings. (1/4-28 UNF flat bottom fitting)

Commercially available fittings

Identification

V - 07 A E P 0 6 - P 01					
① ② ③ ④ ⑤ ⑥					
① Plunger diameter 05: Ø5mm 07: Ø7mm	② Material (Plunger/Cylinder material) A: Al ₂ O ₃ /Al ₂ O ₃ Z: ZrO ₂ /Al ₂ O ₃	③ Pump head material E: ECTFE F: PVDF	④ Flushing port _: Unavailable P: Available	⑤ Joint Adaptation pump 4: Quick fastener..... V-07AF 0: Male thread/Tube..... V-07AEP, V-07AFP 6: Female thread..... V-05ZEP/ZE, V-07AFP/AF	⑥ Volume/shot 01: 0.1mL/shot 02: 0.2mL/shot 03: 0.3mL/shot

Specification

Applications	Model	Joint	Volume/shot mL	Flow range mL/min	Rotation speed rpm	Repeatability	Max. discharge pressure kPa	Mass g
Fuel-cell	V-07AF4	Quick fastener	0.1	1 - 20	10 - 200	±3% or below ^{Note1}	40	About 480
Immunoassay analyzers	V-05ZF(P)66-P	Female thread (1/4-28 UNF)	0.1	0.5 - 30	10 - 300	±1.5% or below ^{Note2}	150	About 820
	V-07AEP06-P01	Male thread	0.1	0.5 - 30	10 - 300	±1.5% or below ^{Note2}	150	About 700
	V-07AEP06-P02		0.2	1 - 60				
	V-07AEP06-P03		0.3	1.5 - 90				
	V-07AF(P)66-P01	Female thread (1/4-28 UNF)	0.1	0.5 - 30	5 - 300	±1.5% or below ^{Note2}	150	About 700
	V-07AF(P)66-P02		0.2	1 - 60				
V-07AF(P)66-P03	0.3		1.5 - 90					
Dialysis machines	V-07AFP06-P01	Tube	0.1	0.5 - 30	5 - 300	±1% or below ^{Note2}	200	About 700
	V-07AFP06-P02		0.2	1 - 60				

• Liquid temperature Other than V-07AFP06-P : 0 - 60°C (Non condensing) V-07AFP06-P : 10 - 40°C (Max flushing temperature is 95°C for 30 min at a maximum.)

• Ambient temperature V-07AF4 : 0 - 60°C V-05ZF(P)66-P, V-07AEP06-P, V-07AF(P)66-P : 0 - 40°C V-07AFP06-P : 0 - 50°C

• Motor V-05 : 2-phase unipolar stepping motor V-07 : Two-phase bipolar stepper motor


• Power voltage : DC24V

Note1 : Variation to an average flow of the operation at 200min-1 with both the suction and discharge valves fully opened.

Note2 : Based on the CCW operation at 100min-1 with opened suction/discharge lines.

Dimensions in mm

AC motor




Model	Standard motor	L1	L2
V-05	AC100V 15W	238 (248) ^{Note}	112 (122) ^{Note}
V-10 □ L1	AC100V 15W	238 (248) ^{Note}	112 (122) ^{Note}
V-10 □ L2	AC100V 25W	247 (258) ^{Note}	117 (128) ^{Note}


Note : Shows the dimensions when the reduction ratio is 1/30 to 1/150.

DC motor


V-07AF4




V-05ZF(P)66-P



V-07AEP06-P V-07AF(P)66-P



V-07AFP06-P



IWAKI CO., LTD. 6-6 Kanda-Sudacho 2-chome Chiyoda-ku Tokyo 101-8558 Japan TEL : (81)3 3254 2935 FAX : 3 3252 8892 IWAKI has global net work. Please find your distributor location at www.iwakupumps.jp

European Headquarter	: IWAKI Europe GmbH	TEL: (49)2154 9254 0	FAX: 2154 9254 48
Germany	: IWAKI Europe GmbH	TEL: (49)2154 9254 50	FAX: 2154 9254 55
The Netherlands	: IWAKI Europe GmbH (Netherlands Branch)	TEL: (31)74 2420011	FAX: (49)2154 925448
Italy	: IWAKI Europe GmbH (Italy Branch)	TEL: (39)0444 371 115	FAX: 0444 335350
Spain	: IWAKI Europe GmbH (Spain Branch)	TEL: (34)93 37 70 198	FAX: 93 47 40 991
Poland	: IWAKI Europe GmbH (East Europe Branch)	TEL: (48)12 347 0755	FAX: 13 67 20 30
Belgium	: IWAKI Belgium N.V.	TEL: (32)13 67 02 00	FAX: 12 347 0900
Denmark	: IWAKI Nordic A/S	TEL: (45)48 24 2345	
Finland	: IWAKI Suomi Oy	TEL: (358)9 2745810	
France	: IWAKI France S.A.	TEL: (33)1 69 63 33 70	FAX: 1 64 49 92 73
Norway	: IWAKI Norge AS	TEL: (47)23 38 49 00	
Sweden	: IWAKI Sverige AB	TEL: (46)8 511 72900	()Country codes

U.S.A.	: IWAKI America Inc.	TEL: (1)508 429 1440	FAX: 508 429 1386
Argentina	: IWAKI America Inc. (Argentina Branch)	TEL: (54)11 4745 4116	
Brazil	: IWAKI Do Brasil Comercio De Bombas Hidraulicas LTDA.	TEL: (55)19 3244 5900	FAX: 19 3244 5900
Singapore	: IWAKI Singapore Pte Ltd.	TEL: (65)6316 2028	FAX: 6316 3221
Indonesia	: IWAKI Indonesia (Indonesia Office)	TEL: (62)21 6906606	FAX: 21 6906612
Malaysia	: IWAKI Sdn. Bhd.	TEL: (60)3 7803 8807	FAX: 3 7803 4800
Australia	: IWAKI Pumps Australia Pty Ltd.	TEL: (61)2 9899 2411	FAX: 2 9899 2421
China (Guangzhou)	: IWAKI Pumps Co., Ltd.	TEL: (852)2607 1168	FAX: 2607 1000
China (Shanghai)	: GFTZ IWAKI Engineering & Trading Co., Ltd.	TEL: (86)20 84350603	FAX: 20 84359181
Korea	: IWAKI Pumps (Shanghai) Co., Ltd.	TEL: (86)21 6272 7502	FAX: 21 6272 6929
Taiwan	: IWAKI Korea Co., Ltd.	TEL: (82)2 2630 4800	FAX: 2 2630 4801
Thailand	: IWAKI Pumps Taiwan Co., Ltd.	TEL: (886)2 8227 6900	FAX: 2 8227 6818
	: IWAKI (Thailand) Co., Ltd.	TEL: (66)2 322 2471	FAX: 2 322 2477

Caution for safety use:
Before use of pump, read instruction manual carefully to use the product correctly.

Actual pumps may differ from the photos. Specifications and dimensions are subject to change without prior notice. For further details please contact us.

Legal attention related to export.

Our products and/or parts of products fall in the category of goods contained in control list of international regime for export control. Please be reminded that export license could be required when products are exported due to export control regulations of countries.

The posting and copying from this catalogue without permission is not accepted firmly.